

| Technical data | | C6000 | |
|--|---------|-------------------------------------|----------|
| | | C6205 | C6205 TS |
| HEADER | | | |
| Width option | | 4.20 / 4.80 / 5.40 / 6.30 | |
| Hydraulic cutting height adjustment | mm | from -300 to +1,370 | |
| Oil-immersed planetary knife drive gearbox (1220 cuts/min.) | | standard | |
| Long right and left crop dividers, fixed | | standard | |
| No. Of crop lifters | | 13 to 20 depending on cutting width | |
| Trailer tow hitch | | standard | |
| Header transport trolley | | optional | |
| Rapeseed header conversion kit with hydraulic controlled side cutter on right | | optional | |
| Side cutter for rapeseed on left with separate hydraulic control (only with rapeseed header) | | optional | |
| Sunflower header conversion kit | | optional | |
| Autocontrol (with lateral float) | | optional | |
| PICK-UP REEL | | | |
| 6-bar reel with hydraulic height adjustment | | standard | |
| Hydraulic horizontal adjustment | | standard | |
| Electrical speed control | rpm | 16 to 45, infinitely variable | |
| TRESHING DRUM | | | |
| Diameter | mm | 600 | |
| Width | mm | 1,270 | |
| Bars | n° | 8 | |
| Electrical variator | rpm | 420 - 1,250 | |
| Threshing drum speed reducer (optional) | rpm | 210 - 625 | |
| CONCAVE | | | |
| Bars | n° | 15 | |
| Wrap angle | degrees | 121 | |
| Separation surfaces | m² | 0.95 | |
| Multi-segment concave | | optional | |
| Adjustment of concave inlet/outlet from the driver's cab | | standard | |
| Conversion for maize harvesting, grain | | optional | |
| TURBO SEPARATOR (TS) | | | |
| Diameter | mm | - | 590 |
| Speed of rotation | rpm | - | 775/410 |
| Mechanical adjustment through 5 positions | | - | standard |
| Separation surface area | m² | - | 0.81 |
| STRAW WALKER | | | |
| Elements | n° | 5 | 5 |
| Steps | n° | 5 | 4 |
| Straw walkers type | | close | |
| Ball bearing mounts | | standard | |
| Shaking surface area | m² | 5.28 | 4.60 |
| Total separation surface | m² | 6.23 | 6.36 |
| STRAW CHOPPER - CHAFF SPREADER | | | |
| Built-in straw chopper with manually adjustable spread width | | optional | |
| Built-in chaff spreader | | optional | |
| CLEANING SYSTEM | | | |
| High performance crossflow fan | | standard | |
| Pre-sieve | | standard | |
| Sieve box illumination | | standard | |
| Total ventilated sieve area | m² | 4.22 | |
| TAILING RETURN SYSTEM | | | |
| Electronic control of returns level and overload | | optional-depending on versions | |
| Independent L/R returns with re-threshing system | | standard | |

| Technical data | | C6000 | |
|---|---------|-------------------|----------|
| | | C6205 | C6205 TS |
| GRAIN TANK | | | |
| Lifting / Capacity | litres | 7000 | |
| Discharge in any position | | standard | |
| Visual and audible grain tank level indicator | | standard | |
| Interior light / Grain sampling from driving position | | standard | |
| Discharge speed | lt/sec. | 75 | |
| ENGINE | | | |
| Tier IV Final water cooled Turbo Diesel engine | | DEUTZ L6 6.1 lt | |
| Power at rated engine speed (97/68/EC) | kW/HP | 169/230 | |
| Maximum power (ECE R120) | kW/HP | 184/250 | |
| Fuel tank | litres | 450 | |
| AdBlue tank | litres | 53 | |
| TRANSMISSION / BRAKES / STEERING | | | |
| Hydrostatic transmission with 3-speed gearbox (105 cc) | | standard | |
| Forward speed / Reverse speed | Km/h | 0 - 26.0 / 0-14.0 | |
| Pedal operated hydraulic brake, usable as independent brake, mechanical parking brake | | standard | |
| TYRES | | | |
| Front, 620 / 75 R30 168 A8 | | standard | |
| Rear, 320/80 R18 | | standard | |
| DIMENSIONS | | | |
| Wheelbase | mm | 3,890 | |
| Length without cutter bar | mm | 8,770 | |
| Length with cutter bar- crop dividers folded | mm | 10,620 | |
| Grain tank height | mm | 3,935 | |
| WEIGHTS | | | |
| without header | Kg | 8,770 | |
| weight with 4.20 m header | Kg | 10,050 | |
| weight with 4.80 m header | Kg | 10,190 | |
| weight with 5.40 m header | Kg | 10,350 | |
| weight with 6.30 m header | Kg | 10,550 | |

